- **1HP PERMANENT MAGNET MOTOR** FOR MAXIMIMUM PERFORMANCE
- **CENTER MOUNT DRUM**
- **POWERS LOAD IN & OUT**
- **AUTOMATIC LOAD HOLDING BRAKE**
- **FREESPOOLING CLUTCH** FOR QUICK WIRE ROPE DEPLOYMENT

Pull, Speed, Amps

Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Current (A)
0	24 (7.3)	18
500 (227)	19 (5.8)	51
1000 (454)	15 (4.6)	88
1500 (680)	14 (4.3)	125
2000 (907)	11 (3.3)	165
2500 (1134)	9 (2.7)	204

Line Pull and Rope Capacity in Layer

Layer	Rated Line Pull lbs (kgs)	Total Rope on Drum ft (m)
1	2500 (1134)	8.2 (2.5)
2	2200 (998)	17.42 (5.3)
3	1930 (875)	27.2 (8.2)
4	1700 (771)	37.7 (11.5)
5	1480 (673)	50 (15.2)

Part# 15006

- **Rated Line Pull:** 2,500 lbs (1134kgs)
- **Motor:** 12V DC 1.0 hp (.75kW)
- **Control:** - Handlebar mounted mini-rocker switch
- **Gear Train:** 3 stage planetary
- **Gear Ratio:** 136:1
- **Clutch:** Freespooling
- **Brake:** Automatic Load Hold
- **Wire Rope Dia x L:** 3/16" x 50' (4.8mm x 15.2m)
- **Drum Dia x L:** 2.0" x 2.9" (51mm x 73mm)
- **Battery Leads:** 6 gauge
- **Overall Dimensions (L x W x H):** 13.5" x 4.3" x 4.5" (343 x 110 x 115mm)
- **Mounting Bolt Pattern:** 4.9" x 3.0" (124 x 76mm)
- **Weight:** N.W. 20.9lbs (9.5kgs)
- 2 Year Limited Warranty

Recommended for Maximum Performance:

- Snatch block/pulley block to double line for loads over 1200lbs

Part# 15014

Identical winch with the following exceptions:

- **Rope:** 9.5mm x 40ft Synthetic vs. Wire
- **Fairlead:** Hawse vs. Roller
- **Hook:** CrMo Sling vs. Alloy Steel